



Filters

F2 Series

- ❖ Compact inline design
- ❖ Maximum working pressure up to 3000 psig (207 bar)
- ❖ Working temperature from -20°F to 900°F (-28°C to 482°C)
- ❖ 316 stainless steel and brass body material
- ❖ Variety of end connections

Features


- ❖ Compact inline design
- ❖ Nominal pore sizes for sintered element: 0.5, 2, 7, 15, 40, 60 and 90 µm
- ❖ Nominal pore sizes for strainer element: 100, 150, 250 and 450 µm
- ❖ Maximum working pressure up to 3000 psig (207 bar)
- ❖ Working temperature from -20°F to 900°F (-28°C to 482°C)
- ❖ Body materials: 316 S.S. 316L S.S. 304 S.S. 304L S.S. 321 S.S. and Brass
- ❖ Variety of end connections

Pressure vs. Temperature

Material	316 S.S.	Brass
Temperature, °F(°C)	Working Pressure, psig (bar)	
-20 (-28) to 100 (37)	3000 (207)	1000 (68.9)
200 (93)	2580 (177)	780 (53.7)
300 (148)	2330 (160)	680 (46.8)
400 (204)	2140 (147)	—
500 (260)	1990 (137)	—
600 (315)	1880 (129)	—
650 (343)	1845 (127)	—
700 (371)	1800 (124)	—
750 (398)	1760 (121)	—
800 (426)	1725 (118)	—
850 (454)	1690 (116)	—
900 (482)	1640 (112)	—

Standard Materials of Construction

Component	Material Grade/ASTM Specification	
	316 S.S.	Brass
1 Inlet Body	316 S.S./A479	Brass C36000/B16
2 Spring	304 S.S./A313	
3 Element	Sintered 316 S.S. or strainer 316 S.S.	
4 Outlet Body	316 S.S./A479	Brass C36000/B16




Maximum Differential Pressure of Clean Filter at 70°F (20°C)

Maximum Differential Pressure psig (bar)										
0.5 micron	2 micron	7 micron	15 micron	40 micron	60 micron	90 micron	100 micron	150 micron	250 micron	450 micron
2250 (155.2)	2250 (155.2)	1950 (134.5)	1750 (120.3)	1150 (79.3)	1150 (79.3)	1000 (68.9)	1000 (68.9)	1000 (68.9)	1000 (68.9)	1000 (68.9)

Elements

Nominal Pore Size μm	Pore Size Range μm	Element Type
0.5	0.5 to 2	Sintered
2	1 to 4	
7	5 to 10	
15	11 to 25	
40	35 to 53	
60	50 to 75	
90	75 to 100	Strainer
100	—	
150	—	
250	—	
450	—	

Dimensions



Basic Ordering Number	Connection Type and Size	Orifice in.(mm)	Filter Series	Dimension, in. (mm)	
				A	B
F2-F2-	1/8" CIR-LOK	0.094 (2.39)	2	2.35 (59.7)	9/16 (14.3)
F2-F4-	1/4" CIR-LOK	0.187 (4.75)	4	2.95 (74.9)	3/4 (19.0)
F2-F6-	3/8" CIR-LOK	0.281 (7.14)	8	3.21 (81.5)	1 (25.4)
F2-F8-	1/2" CIR-LOK	0.406 (10.3)	8	3.49 (88.6)	
F2-M3-	3 mm CIR-LOK	0.094 (2.39)	2	2.38 (60.5)	9/16 (14.3)
F2-M6-	6 mm CIR-LOK	0.187 (4.75)	4	2.96 (75.2)	3/4 (19.0)
F2-FNPT2-	1/8 Female NPT	0.094 (2.39)	2	2.16 (54.9)	9/16 (14.3)
F2-FNPT4-	1/4 Female NPT	0.187 (4.75)	4	2.87 (72.9)	3/4 (19.0)
F2-NPT2-	1/8 Male NPT	0.094 (2.39)	2	1.88 (47.7)	9/16 (14.3)
F2-NPT4-	1/4 Male NPT	0.187 (4.75)	4	2.69 (68.3)	3/4 (19.0)
F2-GFS2-	1/8 Male GFS	0.094 (2.39)	2	2.79 (70.8)	
F2-GFS4-	1/4 Male GFS	0.187 (4.75)	4		
F2-FBT2-	1/8 Female BSPT	0.094 (2.39)	2	2.16 (54.9)	9/16 (14.3)
F2-FBT4-	1/4 Female BSPT	0.187 (4.75)	4	2.87 (72.9)	3/4 (19.0)
F2-MBT2-	1/8 Male BSPT	0.094 (2.39)	2	1.88 (47.7)	9/16 (14.3)
F2-MBT4-	1/4 Male BSPT	0.187 (4.75)	4	2.69 (68.3)	3/4 (19.0)

How to Order

F2 — F6 — M10 — S90 — 316

Filter Series	Inlet Type	Inlet Size	Outlet Type	Outlet Size	Element Type	Element Nominal Pore Size	Body Material
F2	FNPT Female NPT	2 1/8 in.	Same as inlet type and inlet size		S Sintered	05 0.5µm	316 316 S.S.
	NPT Male NPT	4 1/4 in.			T Strainer	2 2µm	316L 316L S.S.
	FBT Female BSPT	6 3/8 in. or 6 mm			7 7µm	304 304 S.S.	
	MBT Male BSPT	8 1/2 in. or 8 mm	If outlet and inlet are the same, eliminate the outlet designator		15 15µm	304L 304L S.S.	
	FMS Female ISO 261	10 10 mm			40 40µm	BR Brass	
	MS Male ISO 261	12 3/4 in. or 12 mm			60 60µm		
	FBP Female BSPP	14 14 mm			90 90µm		
	MBP Male BSPP	16 1 in. or 16 mm			100 100µm		
	F Fractional Tube Fitting	18 18 mm			150 150µm		
	M Metric Tube Fitting	20 1 1/4 in. or 20 mm			250 250µm		
	FSW Fractional Tube Socket Weld	22 22 mm or M22 x1.5			450 450µm		
	FBW Fractional Tube Butt Weld	25 25 mm					
	GFS Male GFS Fitting						