


# Dosing valves

## Series VD type " M " - MEDIUM

### STANDARD



#### Technical data

Rating	PN 16
Connections	Female threaded GAS (FF) - ISO 228 Male threaded GAS (FM) - ISO 228 Hose nipple (PG)
Temperature	from +10 to +100 °C

#### Description


The dosing valves serie VD have been studied and developed to intercept and dose different liquid products ( varnishes, solvents, dyes and inks ). They can be employed in different fields as textile dyeing and finishing plants, printing, general industrial plants. All Burocco valves are delivered after testing and calibration and ready for a long utilize, without maintenance.



Ø Tip	Kvs m <sup>3</sup> /h	Ø Plug	Kvs m <sup>3</sup> /h
0,5 mm	0,003	2,0 mm	0,1
1,6 mm	0,06	7,5 mm	1,5
2,0 mm	0,1	12,0 mm	3,6
4,0 mm	0,3	18,0 mm conical	7
4,0 mm	0,3	22,0 mm	12

Stroke	
Tip	10,0 mm
Plug	19,0 mm

Dosing valves  
**Series VD type "M" - MEDIUM**  
**STANDARD**



Materials	
Valve body	AISI 316/316L
Tip / plug	AISI 316/316L
Stem	AISI 316/316L
Packing	Standard PTFE ring energized with O-ring FPM
Bushing	PTFE
Body gasket	PTFE
Weight	Kg. 3,1

